

U.S.S.N. 10/811,264

-2-

GKNG 1192 PUS

RECEIVED
CENTRAL FAX CENTER

SEP 28 2006

IN THE CLAIMS:

1. (currently amended) A convoluted boot made of an elastic material, and having a longitudinal axis (A), the boot sealing an annular chamber between an outer joint part and a shaft connected to an inner joint part of ~~[[a]]~~ an articulating universal joint and comprising:

a first collar to be fixed to the shaft and a second collar to be fixed to an outer part of the universal joint as well as a boot portion with a plurality of annular folds, which boot portion connects the two collars, wherein each of the annular folds comprises a first annular outer flank facing the first collar and a second annular outer flank facing the second collar, wherein at two adjoining annular folds, a surface of two opposed annular flanks each comprise a plurality of raised portions in the form of burls which project from a uniform annular face, ~~wherein the raised portions comprise burls,~~ and wherein the ~~raised portions~~ burls of the two opposed annular flanks are positioned on circles with different radii.

2. (cancelled)

3. (previously presented) A convoluted boot according to claim 1, wherein the burls are partially spherically shaped.

4. (previously presented) A convoluted boot according to claim 1, wherein the burls comprise a height of approximately 0.05 to 1.3 mm above the uniform annular face.

5. (previously presented) A convoluted boot according to claim 4, wherein, at their base, the burls comprise a diameter of approximately 3 mm.

6. (previously presented) A convoluted boot according to claim 1, wherein the raised portions, in a cross-sectional view, are semi-lenticular in shape.

U.S.S.N. 10/811,264

-3-

GKNG 1192 PUS

7. (previously presented) A convoluted boot according to claim 1, wherein, on the at least one annular flank, the raised portions are uniformly distributed on at least one circle extending coaxially relative to the longitudinal axis (A).

8. (previously presented) A convoluted boot according to claim 7, wherein 20 to 120 raised portions are arranged on one circle.

9. (previously presented) A convoluted boot according to claim 7, wherein the raised portions of one circle are arranged at a maximum distance of 10 mm from one another.

10. (cancelled)

11. (cancelled)

12. (previously presented) A convoluted boot according to claim 7, wherein the raised portions on a first circle are arranged so as to be circumferentially offset from the raised portions on a second circle extending coaxially relative to said first circle.

13. (previously presented) A convoluted boot according to claim 7, wherein two adjoining circles are arranged at a maximum radial distance of 10 mm relative to one another.

14. (currently amended) A convoluted boot made of an elastic material, and having a longitudinal axis (A), the boot sealing an annular chamber between an outer joint part and a shaft connected to an inner joint part of [[a]] an articulating universal joint and comprising:

a first collar to be fixed to the shaft and a second collar to be fixed to an outer part of the universal joint as well as a boot portion with a plurality of annular folds, which boot portion connects the two collars, wherein each of the annular folds comprises a first annular outer flank facing the first collar and a second annular outer flank facing the second collar, wherein at two adjoining annular folds, a surface of two

U.S.S.N. 10/811,264

-4-

GKNG 1192 PUS

opposed annular flanks each comprise a plurality of recesses in the form of indentations which are set back from a uniform annular face, ~~wherein the recesses comprise indentations, and~~ wherein the ~~recesses~~ indentations of the two opposed annular flanks are positioned on circles with different radii.

15. (cancelled)

16. (previously presented) A convoluted boot according to claim 14, wherein the indentations are partially spherically shaped.

17. (previously presented) A convoluted boot according to claim 14, wherein, on the at least one annular flank, the recesses are uniformly distributed on at least one circle extending coaxially relative to the longitudinal axis (A).

18. (previously presented) A convoluted boot according to claim 17, wherein 20 to 120 recesses are arranged on one circle.

19. (previously presented) A convoluted boot according to claim 14, wherein the recesses are arranged to directly adjoin one another.

20. (previously presented) A convoluted boot according to claim 17, wherein the recesses on one circle are arranged so as to be circumferentially offset relative to the recesses on a second circle extending coaxially relative to said first circle.

21. (currently amended) A convoluted boot made of an elastic material, and having a longitudinal axis, the boot sealing an annular chamber between an outer joint part and a shaft connected to an inner joint part of ~~[[a]]~~ an articulating universal joint and comprising:

a first collar to be fixed to the shaft and a second collar to be fixed to an outer part of the universal joint as well as a boot portion with a plurality of annular folds, which boot portion connects the two collars, wherein each of the annular folds comprises a first annular outer flank facing the first collar and a second annular outer

U.S.S.N. 10/811,264

-5-

GKNG 1192 PUS

flank facing the second collar, wherein at two adjoining annular folds, a surface of only one of two opposed annular flanks comprises a plurality of raised portions in the form of burls which project from a uniform annular face, wherein the ~~raised portions~~ burls are positioned on circles with different radii.

22. (currently amended) A convoluted boot made of an elastic material, and having a longitudinal axis, the boot sealing an annular chamber between an outer joint part and a shaft connected to an inner joint part of ~~[[a]]~~ an articulating universal joint and comprising:

a first collar to be fixed to the shaft and a second collar to be fixed to an outer part of the universal joint as well as a boot portion with a plurality of annular folds, which boot portion connects the two collars, wherein each of the annular folds comprises a first annular outer flank facing the first collar and a second annular outer flank facing the second collar, wherein at two adjoining annular folds, a surface of only one of two opposed annular flanks comprises a plurality of recesses in the form of indentations which are set back from a uniform annular face, wherein the ~~recesses~~ indentations are positioned on circles with different radii.